

With 8,700 lumens and a XGA resolution, the EB-Z9870 large venue projector is simple to set-up and benefits from 3LCD technology.

The white EB-Z9870 is an impressive and versatile installation projector, featuring 8,700 lumens brightness and XGA resolution. Able to project portrait aspect images for digital signage, the EB-Z9870 has a flexible installation angle, lens shift for off-centre positioning and plenty of calibration options, with optional Wi-Fi and HDBaseT connectivity.

Clear images and 3LCD technology

At 8,700 lumens the EB-Z9870 is an ultra-bright XGA resolution projector. This projector benefits from Epson's 3LCD technology, which ensures high-quality images with equally high White and Colour Light Output for vivid colours and bright images, even in daylight, and three times brighter colours than competitive projectors¹.

Perfect for large venues

Museums, auditoriums and corporate environments can benefit from the EB-Z9870's large projected image, ideal for making a big impact.

Portrait projection

Able to project portrait aspect images, the EB-Z9870 is ideal for digital signage. Welcome to a whole new way of seeing things; portrait mode is also useful when a venue or event, such a fashion show, doesn't lend itself to landscape projection.

Easy set-up

As well as a flexible installation angle and lens shift for off-centre positioning, the EB-Z9870 includes plenty of calibration options such as edge blending, test patterns and Epson's Super Resolution feature.

Connectivity

The EB-Z9870 includes HDBaseT, which allows up to five connections in one. Optional Wi-Fi is also included for extra flexibility.

Short-throw capability

Great news for auditoriums and lecture theatres; a new and exclusive LU02 short throw lens allows this projector to be positioned closer to the screen.

KEY FEATURES

- High brightness Very bright 8,700 lumens
- Flexible
- Choose different installation angles • 3LCD technology
- For vivid colours and bright images
- Connectivity
- HDBaseT and optional Wi-Fi connectivity
- Portrait projection
 - When landscape isn't suitable





PRODUCT SPECIFICATIONS

TECHNOLOGY	
Projection System	3LCD Technology, RGB liquid crystal shutter
LCD Panel	1,06 inch with C2 Fine
IMAGE	
Colour Light Output	8.700 lumen-7.300 lumen (economy)
•	8.700 lumen - 7.300 lumen (economy)
White Light Output	
Portrait Colour Light Output	8.500 lm
Portrait White Light Output	8.500 lm
Resolution	XGA, 1024 x 768, 4:3
Contrast Ratio	15.000 : 1
Lamp	380 W, 3.000 h durability, 4.000 h durability (economy mode)
Lamp (portrait mode)	304 W, 1.000 Hours Durability
Keystone Correction	Manual vertical: ± 30 °, Manual horizontal ± 30 °
Aspect Ratio	4:3
OPTICAL	
Projection Ratio	1,65 - 2,65:1
Zoom	Motorized, Factor: 1 - 1,61
Lens Shift	Motorized - Vertical ± 56 %, horizontal ± 19 %
Projection Size	60 inches - 500 inches
Projection Lens F Number	1,65 - 2,51
Focal Distance	36 mm - 57,5 mm
Focus	Motorized
Projection Distance Wide	1,9 m - 16,8 m
Projection Distance Tele	3,2 m - 27,2 m
Lens	Optical
Lens	
CONNECTIVITY	USB 1.1 Type & USB 2.0 Type B (Service Only) BS-232C, WI AN Wireless I AN IFFF
	USB 1.1 Type A, USB 2.0 Type B (Service Only), RS-232C, WLAN, Wireless LAN IEEE
CONNECTIVITY	802.11b/g/n (optional), VGA in, VGA out, DVI in, HDMI in, Composite in, Component in, BNC in
CONNECTIVITY Interfaces	
CONNECTIVITY Interfaces GENERAL	802.11b/g/n (optional), VGA in, VGA out, DVI in, HDMI in, Composite in, Component in, BNC in (6x), S-Video in, HDBaseT
CONNECTIVITY Interfaces GENERAL Energy Use	802.11b/g/n (optional), VGA in, VGA out, DVI in, HDMI in, Composite in, Component in, BNC in (6x), S-Video in, HDBaseT 809 W, 721 W (economy), 0,37 W (standby)
CONNECTIVITY Interfaces GENERAL Energy Use Supply Voltage	802.11b/g/n (optional), VGA in, VGA out, DVI in, HDMI in, Composite in, Component in, BNC in (6x), S-Video in, HDBaseT 809 W, 721 W (economy), 0,37 W (standby) AC 100 V - 240 V,50 Hz - 60 Hz
CONNECTIVITY Interfaces GENERAL Energy Use Supply Voltage Product dimensions	802.11b/g/n (optional), VGA in, VGA out, DVI in, HDMI in, Composite in, Component in, BNC in (6x), S-Video in, HDBaseT 809 W, 721 W (economy), 0,37 W (standby) AC 100 V - 240 V,50 Hz - 60 Hz 741 x 534 x 197 mm (Width x Depth x Height)
CONNECTIVITY Interfaces GENERAL Energy Use Supply Voltage Product dimensions Product weight	802.11b/g/n (optional), VGA in, VGA out, DVI in, HDMI in, Composite in, Component in, BNC in (6x), S-Video in, HDBaseT 809 W, 721 W (economy), 0,37 W (standby) AC 100 V - 240 V,50 Hz - 60 Hz 741 x 534 x 197 mm (Width x Depth x Height) 25 kg
CONNECTIVITY Interfaces GENERAL Energy Use Supply Voltage Product dimensions Product weight Noise Level	802.11b/g/n (optional), VGA in, VGA out, DVI in, HDMI in, Composite in, Component in, BNC in (6x), S-Video in, HDBaseT 809 W, 721 W (economy), 0,37 W (standby) AC 100 V - 240 V,50 Hz - 60 Hz 741 x 534 x 197 mm (Width x Depth x Height) 25 kg Normal: 38 dB (A) - Economy: 35 dB (A)
CONNECTIVITY Interfaces GENERAL Energy Use Supply Voltage Product dimensions Product weight Noise Level Temperature	802.11b/g/n (optional), VGA in, VGA out, DVI in, HDMI in, Composite in, Component in, BNC in (6x), S-Video in, HDBaseT 809 W, 721 W (economy), 0,37 W (standby) AC 100 V - 240 V,50 Hz - 60 Hz 741 x 534 x 197 mm (Width x Depth x Height) 25 kg Normal: 38 dB (A) - Economy: 35 dB (A) Storage -10° C - 60° C
CONNECTIVITY Interfaces GENERAL Energy Use Supply Voltage Product dimensions Product weight Noise Level Temperature Humidity	802.11b/g/n (optional), VGA in, VGA out, DVI in, HDMI in, Composite in, Component in, BNC in (6x), S-Video in, HDBaseT 809 W, 721 W (economy), 0,37 W (standby) AC 100 V - 240 V,50 Hz - 60 Hz 741 x 534 x 197 mm (Width x Depth x Height) 25 kg Normal: 38 dB (A) - Economy: 35 dB (A) Storage -10° C - 60° C Operation 20% - 80%, Storage 10% - 90%
CONNECTIVITY Interfaces GENERAL Energy Use Supply Voltage Product dimensions Product weight Noise Level Temperature Humidity Included Software	 802.11b/g/n (optional), VGA in, VGA out, DVI in, HDMI in, Composite in, Component in, BNC in (6x), S-Video in, HDBaseT 809 W, 721 W (economy), 0,37 W (standby) AC 100 V - 240 V,50 Hz - 60 Hz 741 x 534 x 197 mm (Width x Depth x Height) 25 kg Normal: 38 dB (A) - Economy: 35 dB (A) Storage -10° C - 60° C Operation 20% - 80%, Storage 10% - 90% EasyMP Monitor, EasyMP Multi PC Projection, EasyMP Network Projection
CONNECTIVITY Interfaces GENERAL Energy Use Supply Voltage Product dimensions Product weight Noise Level Temperature Humidity	802.11b/g/n (optional), VGA in, VGA out, DVI in, HDMI in, Composite in, Component in, BNC in (6x), S-Video in, HDBaseT 809 W, 721 W (economy), 0,37 W (standby) AC 100 V - 240 V,50 Hz - 60 Hz 741 x 534 x 197 mm (Width x Depth x Height) 25 kg Normal: 38 dB (A) - Economy: 35 dB (A) Storage -10° C - 60° C Operation 20% - 80%, Storage 10% - 90%
CONNECTIVITY Interfaces GENERAL Energy Use Supply Voltage Product dimensions Product weight Noise Level Temperature Humidity Included Software	 802.11b/g/n (optional), VGA in, VGA out, DVI in, HDMI in, Composite in, Component in, BNC in (6x), S-Video in, HDBaseT 809 W, 721 W (economy), 0,37 W (standby) AC 100 V - 240 V,50 Hz - 60 Hz 741 x 534 x 197 mm (Width x Depth x Height) 25 kg Normal: 38 dB (A) - Economy: 35 dB (A) Storage -10° C - 60° C Operation 20% - 80%, Storage 10% - 90% EasyMP Monitor, EasyMP Multi PC Projection, EasyMP Network Projection
CONNECTIVITY Interfaces GENERAL Energy Use Supply Voltage Product dimensions Product weight Noise Level Temperature Humidity Included Software Options	 802.11b/g/n (optional), VGA in, VGA out, DVI in, HDMI in, Composite in, Component in, BNC in (6x), S-Video in, HDBaseT 809 W, 721 W (economy), 0,37 W (standby) AC 100 V - 240 V,50 Hz - 60 Hz 741 x 534 x 197 mm (Width x Depth x Height) 25 kg Normal: 38 dB (A) - Economy: 35 dB (A) Storage -10° C - 60° C Operation 20% - 80%, Storage 10% - 90% EasyMP Monitor, EasyMP Multi PC Projection, EasyMP Network Projection
CONNECTIVITY Interfaces GENERAL Energy Use Supply Voltage Product dimensions Product weight Noise Level Temperature Humidity Included Software Options ADVANCED FEATURES	 802.11b/g/n (optional), VGA in, VGA out, DVI in, HDMI in, Composite in, Component in, BNC in (6x), S-Video in, HDBaseT 809 W, 721 W (economy), 0,37 W (standby) AC 100 V - 240 V,50 Hz - 60 Hz 741 x 534 x 197 mm (Width x Depth x Height) 25 kg Normal: 38 dB (A) - Economy: 35 dB (A) Storage -10° C - 60° C Operation 20% - 80%, Storage 10% - 90% EasyMP Monitor, EasyMP Multi PC Projection, EasyMP Network Projection Document camera, Quick wireless USB key, Wireless LAN unit
CONNECTIVITY Interfaces GENERAL Energy Use Supply Voltage Product dimensions Product weight Noise Level Temperature Humidity Included Software Options ADVANCED FEATURES Security Video Colour Modes	 802.11b/g/n (optional), VGA in, VGA out, DVI in, HDMI in, Composite in, Component in, BNC in (6x), S-Video in, HDBaseT 809 W, 721 W (economy), 0,37 W (standby) AC 100 V - 240 V,50 Hz - 60 Hz 741 x 534 x 197 mm (Width x Depth x Height) 25 kg Normal: 38 dB (A) - Economy: 35 dB (A) Storage -10° C - 60° C Operation 20% - 80%, Storage 10% - 90% EasyMP Monitor, EasyMP Multi PC Projection, EasyMP Network Projection Document camera, Quick wireless USB key, Wireless LAN unit Kensington lock, Security cable hole
CONNECTIVITY Interfaces GENERAL Energy Use Supply Voltage Product dimensions Product weight Noise Level Temperature Humidity Included Software Options ADVANCED FEATURES Security	 802.11b/g/n (optional), VGA in, VGA out, DVI in, HDMI in, Composite in, Component in, BNC in (6x), S-Video in, HDBaseT 809 W, 721 W (economy), 0,37 W (standby) AC 100 V - 240 V,50 Hz - 60 Hz 741 x 534 x 197 mm (Width x Depth x Height) 25 kg Normal: 38 dB (A) - Economy: 35 dB (A) Storage -10° C - 60° C Operation 20% - 80%, Storage 10% - 90% EasyMP Monitor, EasyMP Multi PC Projection, EasyMP Network Projection Document camera, Quick wireless USB key, Wireless LAN unit Kensington lock, Security cable hole

EB-Z9870

WHAT'S IN THE BOX

- Computer cable
- HDMI Cable Clamp
- Power cable
- Remote control incl. batteries
- User's Manual Set



OPTIONAL ACCESSORIES

- Lamp (x2) ELPLP82
- V13H010L82 • Lamp - ELPLP81
- V13H010L81 • 3D Polarizer - ELPPL01
- V12H618A01
- Wireless LAN Adapter (b/g/n) ELPAP07 V12H418P13ZA
- Ceiling Mount (Low) ELPMB25 V12H003B25
- Ceiling Mount (High) ELPMB26 V12H003B26
- HDBaseT Transmitter ELPHD01 V12H547040
- 3D Glasses (Passive for Child, x5) ELPGS02B V12H541B10
- Quick Wireless Connect USB key ELPAP09 V12H005M09

OPTIONAL LENSES

- Lens (ST Off Axis) ELPLU02 V12H004U02
- Lens (Long Throw) ELPLL07 V12H004L07
- Lens (Middle Throw 1) ELPLM06 V12H004M06
- Lens (Middle Throw 2) ELPLM07 V12H004M07
- Lens (Rear Wide) ELPLR04 V12H004R04
- Lens (Wide) ELPLW04
 V12H004W04

LOGISTICS INFORMATION

sku	V11H607040
EAN code	8715946541242
Multiple Order Quantity	1 Units
Country of Origin	China
Pallet Size Euro	4 Units

EB-Z9870

